



## 产品特点/

### Product Features

- 工作温度-50℃~150℃  
Working Temperature
- 出色的电磁屏蔽  
Excellent Electromagnetic  
Shielding
- 可扩展，易安装  
Expandable and Easy to  
Install

**BEMI700** 是由镀锡铜丝 + 橙色 PET 单丝混编而成，具有良好的屏蔽性的同时，有一定耐磨性。

**BEMI700** is made of tin-plated copper wire + orange PET monofilament blended together, which has good shielding properties and wear resistance.

### 产品应用/Applications

**BEMI700** 主要应用于新能源汽车的电池电缆，仪表盘线束，发动机机舱线束。

**BEMI700** is mainly used in battery cables, dashboard harnesses, engine compartment harnesses of new energy vehicles.

我们的工厂已通过 ISO 9001、IATF 16949、ISO 14001、ISO 45001 和 军工 GJB9001C 认证。

Our manufacturing site has been certified by ISO 9001, IATF 16949, ISO 14001, ISO 45001 and military GJB9001C.

# 性能参数/Performance Parameter

检测项目 Test Items	测试方法 Test Method	测试结果 Test Results
屏蔽效能 (30MHz-3GHz) Shielding Effectiveness	GB/T 30142	>60dB
燃烧性能测试 Flammability Test	FMVSS 302	符合 Pass

上述所有测试参数值均为典型值。产品测试报告请详询销售代表。

All the above test parameter values are typical values. For specific product test reports, please consult your sales representative.

## 产品规格/Specifications

型号 Part No.	参考折径 Reference Width (mm)	适用范围 Applicable Range (mm)	包装长度 Reel Length (m/reel)
BEM1700100827	8 ± 3	5-10	150
BEM1700101027	10 ± 3	7-12	150
BEM1700101227	12 ± 3	8-16	150
BEM1700101527	15 ± 3	10-20	50
BEM1700101827	18 ± 4	15-25	50
BEM1700102027	20 ± 4	18-30	50
BEM1700102227	22 ± 4	22-34	50
BEM1700102527	25 ± 4	24-38	50
BEM1700103027	30 ± 4	26-45	30
BEM1700103827	38 ± 5	30-58	30
BEM1700104527	45 ± 6	40-68	30
BEM1700105027	50 ± 8	45-75	30

\*可根据要求裁切固定长度/It can be cut to a fixed length as required.

\*可根据要求订做其它尺寸/Other sizes can be customized upon request.

**RoHS**  
COMPLIANT

**MXTECH**  
Sleeving Products

**Suzhou Mingxin Electronic Technology Co., Ltd.**

1435 Huguang Road, Zhangpu Town, Kunshan City, Suzhou, Jiangsu Province, China. 215321

<https://petsleeving.en.alibaba.com> | <https://szmingxin.en.made-in-china.com>

TEL:0512-57305228 FAX:0512-57558111